

Status of NuMI/MINOS Operations

Gina Rameika
DOE Tevatron Operations Review
March 27, 2007

Outline



- Introduction
- Proton Intensity (2005 2007)
- Operations Performance
- Safety
- Effort
- Computing
- Physics Analysis
- Outlook & Conclusions

Introduction



MINOS uses the NuMI Beam produced by the 120 GeV MI

MINOS operates two detectors


MINOS Near Detector Hall (1.2 km)

Soudan Underground Laboratory (735 km)

MINOS Control Room WH12NW










Proton Intensity




- Physics data set since May 2005: 2.744E20
- Since June 2006: 1.35E20
- This physical year: 1.066E20


Why Protons Matter?

ν_{μ} disappearance

 $\nu_{\mu} \rightarrow \nu_{e}$

3 σ and 90% CL Sensitivity to $\sin^2(2\theta_{13})$






Presently our systematic error is $\sim 1/3$ statistical error; MINOS goal is to get $11x10^{20}$ by end of 2009



NuMI Performance






Operations Performance Issues

Target

- > Beam Power -> Mechanical stress
 - · At 4e13 ppp we have a safety factor of 1.4 with a 1 mm spot size
- Reduce stress and increase the safety factor by increasing the beam spot size
 - When we run greater than 4e13 ppp we will increase the spot size to 1.3 mm





Operations Performance Issues

Spares Inventory

> Most important elements: target and horns

HORNS	PH1-00	PH1-01	PH1-02	PH1-03	PH1-04	PH1-05	PH2-01	PH2-02	PH2-03	PH2-04
in use	proto	in use					in use			
fiducialize (survey)										
instrumentation										
water tank, hangers										
test pulse			2/3							
stripline										
water lines etc										
I.C.+O.C assem										
O.C. silvered										
O.C. coated										
O.C. welds										
O.C. machined										
O.C. blanks										
I.C. silvered										
I.C. coated										
I.C. welds			7/7	3/7	3/7	3/7		6/6	5/6	
I.C. machined										5/7
I.C. blanks										
	•				700kW	700kW				700kW


TARGETS	NT-01	NT-02	NT-03	NT-04
in use	stuck	in use		
fiducialize (survey)				
instrumentation				
hangers				
mount target + baffle				
fab carrier				
fiducialize target				
fab target + baffle				ordered





Operations Performance - Far Detector


Daily detector performance is monitored with cosmics





Operations Performance - Far Detector


Daily detector performance is monitored with cosmics





Operations Performance - Far Detector

Expect only a few beam induced neutrino events per day







Operations Performance - FD

On-Time Averages

FY04 89.3%; FY05 96.1% FY06 93.1% FY07 98.2%




Smooth sailing



Operations Performance - Near Detector


High event rate





Operations Performance - Near Detector

Weekly performance is monitored against a standard baseline





Operations Performance Issues - ND

Front End Electronics

- > MENU (QIE ADC) failures: 0.5 1 per day
 - · Weekly repair cycle
 - Typically 4 7 dead channels (out of ~10K)
 - Negligible impact on data quality
 - 95% of failed cards have been repaired
- > Other component failures rare (~2 per year)
- > Spares
 - MENU: 2.2%
 - OTHFR: 5 10%
 - Engineers recommends producing 500 new MENU and 5 new Keeper modules

LCW Cooling

- Temperature is steadily rising
 - OK for now, but continued increase will reduce the lifetime of the front ends
- > Correlated with rising groundwater temp
- May need to add a chiller (working on a cost estimate)



Safety at NuMI/MINOS

No reportable incidents in past year

- Underground Areas
 - Access controlled by badging and keys
 - > Training verification
 - > Regular Inspections to verify material control requirements
 - Pumps inspected/tested on a monthly basis
 - > FESS conducts annual "top to bottom" infrastructure inspection

Training

- Underground access
 - Underground Training for all areas: Requires annual refresher class (on-line)
 - Includes access control procedures
 - Emergency evacuation
 - PPE
 - Magnetic Field
- NuMI Radiation Areas: add in Rad Worker, LOTOII and Controlled Access (CA)
- MINOS Hall: GERT
- > MUON Alcoves (CA)

NuMI

- Target Hall, Target/Horn repairs require strict observance of ALARA (component activation)
- Target Hall tritium monitoring/mitigation plan in place
- MINOS Hall
 - New Projects (i.e. MINERVA exp)
 - Hazard Analysis, Work Planning
 - · Newly formed Cryo Review Committee



Safety at Soudan

Safety at the Soudan Underground Lab is the responsibility of the University of Minnesota

- Lab Safety Plan
 - Documents approved by U of M Occupational Safety Department, DNR regional safety officer and Fermilab ES&H
- Joint Safety Review Committee (meets monthly)
 - Review on-site issues with U of M and DNR
- Experimental Planning Committee
 - · Review new experiments that want to move to Lab
- Monthly inspections
 - Cranes, fork lifts, trucks, fire extinguishers, emergency lights
- Yearly inspections
 - University Occupational Safety and Health
 - University Code Officials
 - University Radiation Safety
 - Fermilab ES & H- Keith Schuh
 - Rutherford National Lab-Health and Safety Division
 - Minnesota DNR Regional Safety Officer
- Yearly inspections by outside experts
 - Fire alarm and sprinkler system
 - > Fire extinguishers
 - > Elevator




Technical and Scientific Manpower

- Soudan Underground
 - 8 FTE (Facility, MINOS, CDMS)
 - M-F 7:30am 5:00 pm
 - 24/7 on-call (16/69 MINOS related in FY06)
- > Fermilab (WH12NW Control Room)
 - · 24/7; (4) 7-hr shifts; 1 hr overlap (2 persons) on each end
 - On-site Run Coordinator


Maintenance and Repairs


- > Far Detector
 - Minecrew (daily)
 - UMD (Operation's Manager & Detector Control experts, weekly)
 - UK DAQ experts (periodic)
- > Near Detector
 - Local (resident) physicists electronics repair (available daily)
 - Argonne engineer/technicians (as needed)
 - IIT technical support (as needed)



Collaboration Shift Requirements

- Author list updated annually
- Shift need determined by running schedule
- Institutional shift responsibility determined by # of authors
- Sign up voluntary
- Unfilled shifts get filled by assignment to institutions with lowest fulfilled quota





DAQ Maintenance and Support

Responsibility of UK Collaborators

- > One full time person available 100% to DAQ issues
 - This level is generally not needed, so this person does work on other projects
- > 5 additional UK experts available at a fraction of their time, summing to approximately a second FTE
- > UK provides 24/7 on-call support via YELL-DAQ
- These groups conduct periodic, on-site, scheduled maintenance
 - ~35% of an FTE last year
- > UK groups have financial responsibility for DAQ hardware

System Performance

- > Very low hardware failure rate
 - 1 2 processors per year
 - Usually associated with power interruptions
- > Use shutdowns to install system upgrades



Offline Computing

General Strategy

- ➤ Integrate MINOS systems into central lab facilities as much as possible
 - Dedicated ASF disk space managed by Central Services in CD
 - Linux cluster (25 nodes) administered by Fermilab Experiments Facilities dept in CD
 - Use LSF batch node but are migrating to FermiGrid
 - Oracle Database (used for SAM handling) supported by the Database Administrators department
 - Dedicated poole of Dcashe disk managed by Storage Service Administration in CD
 - 8 Tbytes in AFS, 15 Tbytes in Dcashe
 - 1.1 M files and 73 Tbytes in the Enstore Tape Robot
 - Use FermiGrid for reconstruction

共

Offline Computing

Far Detector

- Record and reconstruct all cosmics (plane and energy triggers)
- Record and reconstruct all activity within the beam spill window
- Near Detector
 - > All cosmics (10/12 plane trigger) recorded
 - > reconstruct 1/6 of cosmics
 - > Record and reconstruct all events in beam spill
- Data acquisition and analysis of beamline data integrated into the processing of raw data
 - > Spill timing
 - > Protons on target
 - > Status and values of beamline devices

类

Offline Computing

Major Activities

- > Calibration
 - Full calibration done for 1st physics set (1.27e20)
 - Second round to be done for data through April 1
 - Time/manpower intensive -> 1/year full update
- > Monte Carlo
 - Just finished our 3rd major update/release
 - ~ 3 month job to meet major needs
- > Reconstruction
 - Also just finished our 3rd major update/release
 - 1 2 months for all data reprocessing

Strategy

Major releases and reprocessing done on ~ an annual basis

*


Computing Resources

Effort

- > Computing Division
 - 1.5 persons dedicated to MINOS support of daily computing operations and control room systems
 - 1 person dedicated to MINOS software infrastructure
 - 1 physicist serves as liason between experiment and CD
- > Collaboration (includes FNAL researchers)
 - Core Off-line Software -> reconstruction
 - Raw data processing -> standard reconstruction ntuple (data and MC)
 - Calibration (cosmic rays, test beam correlation, light injection)
 - Physics analysis groups produce reduced Analysis Ntuples
- Off Site CPU power Monte Carlo Production
 - > 350 Ghz
 - Rutherford/Caltech (Near)
 - William & Mary (56Ghz) (Far)
 - > Additional 224Ghz coming soon at Tufts
 - > Need ~ 3mos to run most of the requested MC data sets


Physics Analysis


Oscillation Results for 1.27E20 p.o.t



- Strong energy-dependent suppression of ν_{μ} events observed (5.9 standard deviation effect below 5 GeV)
- Consistent with the neutrino oscillation hypothesis
- With more data, we can test and rule out alternative hypotheses, such as neutrino decay, which predict a different energy dependent suppression of the ν_{μ} rate

Phys. Rev. Lett. 97 (2006) 19180





类

Physics Analysis Groups

- v_{μ} CC disappearance : Δm_{32}^2 and $\sin^2(2\theta_{23})$
 - > An updated analysis will be presented this summer with a factor of two larger exposure
- Neutral Currents : Set limits on f_{sterile}
 - > Collaboration has blessed the "ND" NC spectrum
 - > Plan 1st "box opening" this summer
- Electron neutrinos
 - \triangleright v_e search will see a signal if θ_{13} is around the Chooz limit
- Beam v_{μ} -bar
 - > Measure oscillations -> Limits on CPT invariance
- Atmospheric neutrinos (v + v-bar + v_e)
 - > v-induced muon events + contained vertex events (1st results on 2-3 years of exposure)
 - Now doing a combined analysis
 - Doubled statistics in ~ 3years
- Cosmic rays (13/sec Near; 1/2sec Far)
 - Charge sign, seasonal variations, moon/sun shadow
- Near Detector Physics
 - > Millions of events in a broad band beam
 - \triangleright Cross sections : v + v-bar + v_e

关

Publications

Charge-separated atmospheric neutrino-induced muons in the MINOS far detector. By MINOS Collaboration. FERMILAB-PUB-07-012-E, BNL-77481-2007-JA, Jan 2007. 14pp. e-Print Archive: hep-ex/0701045 - accepted to PRD

- Observation of muon neutrino disappearance with the MINOS detectors and the NuMI neutrino beam. By MINOS Collaboration (D.G. Michael et al.). FERMILAB-PUB-06-243, BNL-76806-2006-JA, Jul 2006. 6pp. Published in Phys.Rev.Lett.97:191801,2006. e-Print Archive: hep-ex/0607088
- First observations of separated atmospheric nu(mu) and antinu(mu) events in the MINOS detector. By MINOS Collaboration (P. Adamson et al.). FERMILAB-PUB-05-525, Dec 2005. 18pp. Published in Phys.Rev.D73:072002,2006. e-Print Archive: hep-ex/0512036

In preparation :

- Measurement of the Atmospheric Muon Charge Ratio at TeV energies with MINOS
- Measurement of Neutrino Velocity with the MINOS detectors and NuMI Neutrino Beam
- > PRD of 1st oscillation measurement



Outlook & Conclusions

- MINOS Near and Far Detectors operate at high efficiency with low maintenance and repair demands
- The MINOS collaboration is maintaining smooth operations with a shift program that meets the needs of the experiment
 - > Continued support for University Groups is essential for collaborators to be able to maintain this support
- NuMI performance is good, but increased POT/spill and reliable 2.2 sec cycle time is necessary to reach physics goals
- MINOS data is reconstructed and available for physics analysis within days of being taken